

## Umrechnung AWG in Querschnitt

AWG	Durchm. mm	Querschn. mm <sup>2</sup>		AWG	Durchm. mm	Querschn. mm <sup>2</sup>
1	7,350	42,400		23	0,573	0,2590
2	6,540	33,600		24	0,511	0,2050
3	5,820	26,600		25	0,455	0,1630
4	5,190	21,200		26	0,405	0,1280
5	4,620	16,800		27	0,361	0,1020
6	4,110	13,300		28	0,321	0,0804
7	3,670	10,600		29	0,286	0,0646
8	3,260	8,350		30	0,255	0,0503
9	2,910	6,620		31	0,226	0,0400
10	2,590	5,270		32	0,203	0,0324
11	2,300	4,150		33	0,180	0,0260
12	2,050	3,310		34	0,160	0,0200
13	1,830	2,630		35	0,142	0,0160
14	1,620	2,080		36	0,127	0,0127
15	1,450	1,650		37	0,114	0,0100
16	1,290	1,3100		38	0,102	0,0081
17	1,150	1,0400		39	0,089	0,0060
18	1,024	0,8230		40	0,079	0,0049
19	0,912	0,6530		41		
20	0,812	0,5190		42	0,064	0,0032
21	0,723	0,4120		43		
22	0,644	0,3250		44	0,051	0,0020

Letz1te Aktualisierung 28.04.2003  
Durch Dieter Achenbach